

UT256 series are high reliable, true RMS fork meters. Its unique design allows users to measure current by simply moving the wire of interest inside the opening of the 'fork' to the labeled mark. With no mechanical parts, these meters bare no risk from any type of mechanical failure.



UT256A



UT256B

Characteristics	Range	UT256A	UT256B
Certificates	CE, UKCA, cETLus		
AC current (A)	200A	±(1.8%+5)	±(2.5%+5)
DC current (A)	200A		±(2.5%+5)
AC voltage (V)	750V		±(1.2%+3)
	1000V	±(1.2%+3)	
DC voltage (V)	1000V	±(0.8%+3)	±(0.8%+3)
Resistance (Ω)	60MΩ	±(1%+2)	±(1%+2)
Capacitance (F)	60mF		±(4%+20)
Frequency (Hz)	10~10kHz	±(0.1%+5)	
Display count		6000	6000
Diode test	About 3V		√
NCV		√	√
Zero mode			√
Relative mode			√
Category ratings	CAT II 1000V, CAT III 600V		

Features	
Auto range	Continuity buzzer
True RMS	Low battery indication: ≤2.4V
Data hold	Input protection
Auto power off	LCD backlight

Characteristics	
Standard accessories	Batteries, test leads, English manual
Power	1.5V battery (LR6) x 2
Display	UT256A: 35 x 26mm; UT256B: 36.5 x 24mm
Product size	UT256A: 217 x 58.8 x 38.5mm; UT256B: 210 x 53 x 35mm
Product net weight	248g
Standard individual packing	Gift box, carrying bag
Standard quantity per carton	20pcs
Standard carton measurement	485 x 310 x 205mm
Standard carton gross weight	9.5kg